

A8859 - CENIT MATT BASE BL

BARI	
SEC	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: A8859 - CENIT MATT BASE BL
1.1	Other means of identification:
1.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Paint. For industrial user only.
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
	Barpimo, S.A.
	San Fernando, 116 26300 Nájera - La Rioja - España
	Phone.: +34 941 410 000 - Fax: +34 941 410 111
	fds@barpimo.com
1.4	www.barpimo.com Emergency telephone number: +34 941 410 000 (sólo disponible en horario de oficina)
CEC	
SEC	TION 2: HAZARDS IDENTIFICATION **
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Flam. Liq. 3: Flammable liquids, Category 3, H226
	STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
2.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Warning
	Hazard statements:
	Flam. Liq. 3: H226 - Flammable liquid and vapour.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
	Precautionary statements:
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P280: Wear protective gloves/protective clothing/eye protection/face protection. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
	P403+P233: Store in a well-ventilated place. Keep container tightly closed.
	P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment Supplementary information:
	EUH066: Repeated exposure may cause skin dryness or cracking.
	EUH000. Repeated exposure may cause skill dryless of clacking. EUH208: Contains 2-butanone oxime, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
	Substances that contribute to the classification
	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7; 1-methoxy-2-propanol
2.3	Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable



A8859 - CENIT MATT BASE BL

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixture:

Chemical description: Miscellaneous products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS:	64742-48-9	Naphtha (petroleum)), hydrotreated heavy, < 0.1 % EC 200-753-7(1) ATP ATP01			
EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16- XXXX		Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	9,9 - <19,9 %		
CAS:	64742-48-9	Naphtha (petroleum)), hydrotreated heavy, < 0.1 % EC 200-753-7 ⁽¹⁾ ATP ATP01			
	265-150-3 649-327-00-6 01-2119486659-16- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; EUH066 - Danger	9,9 - <19,9 %		
CAS:	107-98-2	1-methoxy-2-propan	ol(1) ATP ATP01			
	203-539-1 603-064-00-3 : 01-2119457435-35- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	2,4 - <4,9 %		
CAS: EC:	108-65-6	2-methoxy-1-methylethyl acetate ⁽²⁾ ATP ATP01				
Index:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	0,9 - <2,4 %		
CAS:	96-29-7	2-butanone oxime ⁽¹⁾	ATP ATP15			
	202-496-6 616-014-00-0 01-2119539477-28- XXXX	Regulation 1272/2008	Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	0,24 - <0,9 %		
CAS:	22464-99-9	2-ethylhexanoic acid	, zirconium salt ⁽¹⁾ Self-classified			
	245-018-1 Non-applicable 01-2119979088-21- XXXX	Regulation 1272/2008	Repr. 2: H361d - Warning	<0,24 %		
CAS:	136-52-7	Cobalt bis(2-ethylhe	xanoate) ⁽¹⁾ Self-classified			
	205-250-6 Non-applicable 01-2119524678-29- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger			
CAS:	34590-94-8	Dipropylene Glycol M	lethyl Ether ⁽²⁾ Not classified			
	252-104-2 Non-applicable 01-2119450011-60- XXXX	Regulation 1272/2008		<0,24 %		

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

(2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.


By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:



A8859 - CENIT MATT BASE BL

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

Most important symptoms and effects, both acute and delayed: 4.2

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media: 5.1

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: 6.1

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

Environmental precautions: 6.2

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

Methods and material for containment and cleaning up: 6.3

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 **Reference to other sections:**

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:



SECTION 7: HANDLING AND STORAGE (continued)

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m ³	
CAS: 107-98-2 EC: 203-539-1	IOELV (STEL)	150 ppm	568 mg/m ³	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
Dipropylene Glycol Methyl Ether	IOELV (8h)	50 ppm	308 mg/m ³	
CAS: 34590-94-8 EC: 252-104-2	IOELV (STEL)			

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-150-3	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-150-3	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Non-applicable



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
2-butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 96-29-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,9 mg/m ³
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	6,49 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	32,97 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m ³
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable

DNEL (General population):

			exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-150-3	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-150-3	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
2-butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 96-29-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,43 mg/m ³
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	4,51 mg/kg	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	3,25 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	8,13 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	0,175 mg/kg	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m ³
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
PNEC:					
Identification					
1-methoxy-2-propanol	STP	100 mg/L	Fresh water		10 mg/L
CAS: 107-98-2	Soil	4,59 mg/kg	Marine water		1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh	water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine	e water)	5,2 mg/kg



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification					
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L	
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L	
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg	
2-butanone oxime	STP	177 mg/L	Fresh water	0,256 mg/L	
CAS: 96-29-7	Soil	0,052 mg/kg	Marine water	0,026 mg/L	
EC: 202-496-6	Intermittent	0,118 mg/L	Sediment (Fresh water)	1,012 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,101 mg/kg	
Cobalt bis(2-ethylhexanoate)	STP	0,37 mg/L	Fresh water	0,00062 mg/L	
CAS: 136-52-7	Soil	10,9 mg/kg	Marine water	0,00236 mg/L	
EC: 205-250-6	Intermittent	Non-applicable	Sediment (Fresh water)	53,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	69,8 mg/kg	
Dipropylene Glycol Methyl Ether	STP	4168 mg/L	Fresh water	19 mg/L	
CAS: 34590-94-8	Soil	2,74 mg/kg	Marine water	1,9 mg/L	
EC: 252-104-2	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg	

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

 body protection				
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.



A8859 - CENIT MATT BASE BL

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

	JN 8: EXPOSURE	CONTIN					
	Pictogram		PPE	Labelling	CEN Standard		Remarks
	Mandatory foot protection	protection risk, with resist	y footwear for against chemical antistatic and heat ant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	R	eplace boots at any sign of deterioration.
F	Additional emerge	ency mea	sures				
	Emergency mea	asure	SI	andards	Emergency measu	ıre	Standards
	Emergency sho	ower		SI Z358-1 11, ISO 3864-4:20	011 Eyewash station	S	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
E	Environmental exp	osure co	ontrols:				
s \	pillage of both the p /olatile organic co	roduct ar mpound	nd its container. s:	For additional i	nformation see subsection		mmended to avoid environmental
۷	-	ive 2010/			llowing characteristics:		
	V.O.C. (Supply):		-	% weight			
	V.O.C. density at		-)4 kg/m³ (437	,04 g/L)		
	Average carbon n		8,27				
	Average molecula	r weight:	125,5	5 g/mol			
	Appearance: Physical state at 20 °	c		Liqu	• 4		
	••	c			• 4		
	Appearance:			Visc			
	Colour:			Cha	racteristic		
C	Odour:			Not	available		
(Odour threshold:			Non	-applicable *		
١	/olatility:						
E	Boiling point at atmos	spheric pi	ressure:	145	٥C		
١	/apour pressure at 2	0 °C:		625	Ра		
١	/apour pressure at 5	0 °C:		344	5,92 Pa (3,45 kPa)		
E	Evaporation rate at 2	0 ºC:		Non	-applicable *		
F	Product description	n:					
0	Density at 20 ºC:			1260) kg/m³		
F	Relative density at 20) °C:		1,26	i		
0	Dynamic viscosity at	20 ºC:		Non	-applicable *		
k	Kinematic viscosity at	: 20 °C:		Non	-applicable *		
k	Kinematic viscosity at	: 40 °C:		>20	,5 cSt		
C	Concentration:			Non	-applicable *		
F	oH:			6 - 1	10		
١	/apour density at 20	°C:		Non	-applicable *		
E	Partition coefficient n	-octanol/	water 20 °C:	Non	-applicable *		
г							

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Solubility in water at 20 °C:



A8859 - CENIT MATT BASE BL

SECT	Ion 9: Physical and chemical	PROPERTIES (continued)
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	30 °C
	Heat of combustion:	Non-applicable *
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	200 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product,	not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity		
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable		
	10.5 Incompatible materials:						
10.5	Incompatible materials	:					
10.5	Incompatible materials Acids	Water	Oxidising materials	Combustible materials	Others		

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:



A8859 - CENIT MATT BASE BL

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

IARC: Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200-753-7 (3); Talc (3); Polyethylene wax (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Cobalt bis(2-ethylhexanoate) (2B)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as
 - it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Ad	ute toxicity	Genus
1-methoxy-2-propanol	LD50 oral	>2000 mg/kg	
CAS: 107-98-2	LD50 dermal	>2000 mg/kg	
EC: 203-539-1	LC50 inhalation	>20 mg/L (4 h)	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	LD50 oral	15000 mg/kg	Rat
CAS: 64742-48-9	LD50 dermal	3160 mg/kg	Rabbit
EC: 265-150-3	LC50 inhalation	>20 mg/L (4 h)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	A	cute toxicity	Genus
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	LD50 oral	15000 mg/kg	Rat
CAS: 64742-48-9	LD50 dermal	3160 mg/kg	Rabbit
EC: 265-150-3	LC50 inhalation	>20 mg/L (4 h)	
2-butanone oxime	LD50 oral	100 mg/kg	
CAS: 96-29-7	LD50 dermal	1100 mg/kg	
EC: 202-496-6	LC50 inhalation	>20 mg/L	
2-ethylhexanoic acid, zirconium salt	LD50 oral	2043 mg/kg	Rat
CAS: 22464-99-9	LD50 dermal	>2000 mg/kg	
EC: 245-018-1	LC50 inhalation	>5 mg/L	
Cobalt bis(2-ethylhexanoate)	LD50 oral	>2000 mg/kg	
CAS: 136-52-7	LD50 dermal	>2000 mg/kg	
EC: 205-250-6	LC50 inhalation	>5 mg/L	
Dipropylene Glycol Methyl Ether	LD50 oral	>2000 mg/kg	
CAS: 34590-94-8	LD50 dermal	>2000 mg/kg	
EC: 252-104-2	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
CAS: 64742-48-9	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
EC: 265-150-3	EC50	Non-applicable		
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
2-ethylhexanoic acid, zirconium salt	LC50	270 mg/L (96 h)	N/A	Fish
CAS: 22464-99-9	EC50	Non-applicable		
EC: 245-018-1	EC50	Non-applicable		
Cobalt bis(2-ethylhexanoate)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 136-52-7	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 205-250-6	EC50	>0.1 - 1 mg/L (72 h)		Algae
Dipropylene Glycol Methyl Ether	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 34590-94-8	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
EC: 252-104-2	EC50	Non-applicable		

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 64742-48-9	COD	Non-applicable	Period	28 days
EC: 265-150-3	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
2-butanone oxime	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 96-29-7	COD	Non-applicable	Period	28 days
EC: 202-496-6	BOD5/COD	Non-applicable	% Biodegradable	24 %
2-ethylhexanoic acid, zirconium salt	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 22464-99-9	COD	Non-applicable	Period	28 days
EC: 245-018-1	BOD5/COD	Non-applicable	% Biodegradable	99 %
Dipropylene Glycol Methyl Ether	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 34590-94-8	COD	0 g O2/g	Period	28 days
EC: 252-104-2	BOD5/COD	Non-applicable	% Biodegradable	73 %

12.3 Bioaccumulative potential:

Identification	Bioac	Bioaccumulation potential		
1-methoxy-2-propanol	BCF	3		
CAS: 107-98-2	Pow Log	-0.44		
EC: 203-539-1	Potential	Low		
2-methoxy-1-methylethyl acetate	BCF	1		
CAS: 108-65-6	Pow Log	0.43		
EC: 203-603-9	Potential	Low		
2-butanone oxime	BCF	5		
CAS: 96-29-7	Pow Log	0.59		
EC: 202-496-6	Potential	Low		
2-ethylhexanoic acid, zirconium salt	BCF			
CAS: 22464-99-9	Pow Log	2.96		
EC: 245-018-1	Potential			
Dipropylene Glycol Methyl Ether	BCF	1		
CAS: 34590-94-8	Pow Log	-0.06		
EC: 252-104-2	Potential	Low		

12.4 Mobility in soil:

Identification	Absorpti	on/desorption	Volatility	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Кос	100	Henry	Non-applicable
CAS: 64742-48-9	Conclusion	High	Dry soil	Non-applicable
EC: 265-150-3	Surface tension	Non-applicable	Moist soil	Non-applicable
2-butanone oxime	Кос	3	Henry	Non-applicable
CAS: 96-29-7	Conclusion	Very High	Dry soil	Non-applicable
EC: 202-496-6	Surface tension	2,57E-2 N/m (25 °C)	Moist soil	Non-applicable
2-ethylhexanoic acid, zirconium salt	Кос	Non-applicable	Henry	2,94E-1 Pa·m ³ /mol
CAS: 22464-99-9	Conclusion	Non-applicable	Dry soil	Yes
EC: 245-018-1	Surface tension	Non-applicable	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)					
08 01 11*	08 01 11* waste paint and varnish containing organic solvents or other hazardous substances Dangerous						
Type of was	Type of waste (Regulation (EU) No 1357/2014):						
HP3 Flammab	le						



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to A	DR 202	1 and RID 2021:	
	14.1	UN number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
$\langle \simeq \rangle$		Labels:	3
	14.4	Packing group:	III
3	14.5	Environmental hazards:	No
	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7		Non-applicable
		to Annex II of Marpol and	
-		the IBC Code:	
-	-	us goods by sea:	
With regard to IN	4DG 39	-18:	
		UN number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.2	UN proper shipping name: Transport hazard class(es):	PAINT 3
	14.2 14.3	UN proper shipping name: Transport hazard class(es): Labels:	PAINT 3 3
	14.2 14.3 14.4	UN proper shipping name: Transport hazard class(es): Labels: Packing group:	PAINT 3 3 III
	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant:	PAINT 3 3
3	14.2 14.3 14.4	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user	PAINT 3 3 III No
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations:	PAINT 3 3 III No 223, 955, 163, 367
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable
3	14.2 14.3 14.4 14.5	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Transport in bulk according	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L
3	14.2 14.3 14.4 14.5 14.6	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Transport in bulk according to Annex II of Marpol and	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable
Transport of da	14.2 14.3 14.4 14.5 14.6 14.7	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Transport in bulk according to Annex II of Marpol and the IBC Code:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable
Transport of da With regard to IA	14.2 14.3 14.4 14.5 14.6 14.7	UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Transport in bulk according to Annex II of Marpol and the IBC Code: us goods by air:	PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9 5 L Non-applicable

A8859 - CENIT MATT BASE BL

SECTION 14: TRANS	CTION 14: TRANSPORT INFORMATION (continued)					
	14.1	UN number:	UN1263			
JHL I	14.2	UN proper shipping name:	PAINT			
	14.3	Transport hazard class(es):	3			
		Labels:	3			
3	14.4	Packing group:	III			
•	14.5	Environmental hazards:	No			
	14.6	Special precautions for user				
		Physico-Chemical properties:	see section 9			
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable			

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH,			

etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration,

- artificial snow and frost,

- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,

- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

** Changes with regards to the previous version



SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Substances that contribute to the classification (SECTION 2):

Removed substances

2-butanone oxime (96-29-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

Pictograms

Hazard statements

· Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312 - Harmful in contact with skin.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 1B: H360 - May damage fertility or the unborn child.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.